



ITX-B305_N126L

- Intel® Alder Lake N97 / N100 / N305
- 1* SODIMM DDR4 slot
- 1* SATA3.0, 1* mSATA, 1 * M.2 SSD port
- 1* HDMI, 1 * VGA, 1* LVDS/ EDP
- 2* LAN, 6 * RS232(2* RS485/ RS422), 2* USB3.0, 6* USB2.0
- 1* M.2 WiFi, 1* M.2 5G slot
- 170 x 170mm
- DC 12V



EPIC-EH305_N126L

- Intel® Alder Lake N97 / N100 / N305
- 1* SODIMM DDR4 slot
- 1* 7pin SATA, 1* MSATA SSD port
- 2* HDMI1.4, 1* LVDS/ EDP
- 2* LAN, 4* USB3.0, 3* USB2.0, 6* RS232 (2* RS485/ RS422)
- 1* M.2 WiFi slot
- 148 x 102mm
- DC 12V



ITX-YS140R1_I526L

- Intel® Meteor Lake Core™ Ultra 5 125H, 14 cores CPU, TDP 28W
- 2*SODIMM DDR5 RAM slots, 5600MHz, up to 96GB
- 2* RTL8111H GbE LAN
- 1* HDMI, 1* DP, 1* LVDS (EDP / LVDS selectable via jumper)
- 4* USB3.0, 4* USB2.0, 6* RS232(2* RS485, 2* RS422)
- 1* M.2 support PCIE X4 SSD, 1* M.2 WiFi
- 170 x 170mm
- DC 12V



STX-T97_2L

- Onboard Intel® Alder Lake-N N97
- 1* SODIMM DDR4 slot, up to 32GB
- 2* LAN (RTL8111H)
- 1* VGA, 1* HDMI, 1* LVDS / EDP port
- 2* USB3.0, 2* USB2.0, 1* RJ45 RS232, 1* RS232 pin port
- 1* PS/2, 1*TPM
- 120 x 120mm
- DC 12V



ITX-YS610R1

- H610 Chipset, support Intel® LGA1700 12th/ 13th/ 14th Gen CPU
- 2* SODIMM DDR4 slots
- 2* SATA3.0 slots , 1* M.2 SSD port
- 1* HDMI1.4, 1* DP, 1* LVDS
- 2* LAN, 6* RS232 (1* RS485/ RS422), 4* USB3.0 (5Gbps), 4* USB2.0
- 1* M.2 WiFi slot
- 170 x 170mm
- DC 19V



AI58J

- Rockchip® RK3588, NPU, up to 6 TOPS
- Onboard LPDDR4 8GB memory, eMMC 64G SSD
- 1* SATA3.0 hard disk port
- 1* HDMI-OUT, 1* HDMI-IN, 1* EDP, 1* LVDS, V-BY-ONE port
- 2* LAN, 2* USB3.0, 4* USB2.0, 6* RS232 (2* RS485)
- Onboard WiFi6/BT chipset
- 148 x 102mm
- DC 12V



VS590+VS250-U8

- Support Intel® LGA1151 / LGA1200 / LGA1700 6th ~ 13th Gen CPU
- 2* SODIMM DDR4 RAM slots, up to 128GB
- 1* VGA, 1* HDMI
- 2* LAN (Intel® I210AT)
- 1* M.2 SSD slot
- 1* PCIE3.0 X16 slot
- 6* USB3.0 + 8* USB3.0 expansion (2A)
- 170 x 170mm
- ATX power supply



PL680_I526L

- Onboard Intel® I5-7200U 2.5GHz dual core processor,TDP 15W
- 1* SODIMM DDR4 RAM slot, 2133MHz, up to 32GB
- 1* HDMI1.4, 1* LVDS, 2* EDP (support dual EDP, or LVDS+EDP display)
- 2* LAN (RTL8111H)
- 2* DB9 RS232/RS485, 4* RS232 pin port
- 4* USB3.0, 4* USB2.0, 1* TPM2.0 port
- 1* M.2 SSD, 1* M.2 WiFi port, 1* Mini PCIE support WiFi/4G
- 148 x 102mm
- DC 12V



VS391M +VS250-P4

- Intel® Z390 chipset, support LGA1151 8th/9th Gen CPU
- 4* DDR4 DIMM RAM slots, up to 64GB
- 1* VGA, 2* HDMI1.4
- 2*LAN (Intel® I210AT)+ 4* POE expansion
- 4* SATA3.0, 1* M.2 SSD port
- 1* PCIE3.0 X16, 1* PCIE3.0 X4, 5* PCI
- 6* USB3.0, 5*USB2.0, 6* RS232(2*RS485/RS422)
- ATX power supply



Z882FM

- Support Intel® Arrow Lake LGA 1851 Ultra2-S Processor
- Intel® Q870/W880 chipset
- 4* DDR5 DIMM RAM slots, 6400MHz, up to 256GB, support ECC memory
- 4* HDMI2.0 (4096x2160 @60Hz), 1*VGA (1920x1080@60Hz)
- 3* LAN (2* Intel® I210AT; 1* Intel® I226LM, support VPRO)
- 6* RS232 (2*RS485/RS422), 10* USB3.0, 3* USB2.0
- 2* PCIE5.0 X16 (X8 signal), 4* PCIE4.0X4, 1* PCI
- 305 x 245mm
- ATX power supply



YENTEK Europe Built for Demanding Environments

With over two decades of experience, YENTEK designs and manufactures robust, **scalable hardware solutions** trusted in demanding industrial environments. **Backed by Intel® IoT Solutions Alliance membership and Intel® Titanium Partner status, YENTEK offers Embedded and Industrial Computers, Panel PCs, Mini PCs, and Industrial Motherboards.**

YENTEK solutions are widely used in AI Edge Computing, Machine Vision, Industrial Automation, Smart Healthcare, Smart Transportation, Cloud Infrastructure, Network Security, Digital Display, and Self-Service applications.

yentek.eu • info@yentek.eu

SCAN ME





AS35-HV

- Rockchip® RK3568B2
- onboard LPDDR4 4GB, eMMC5.1 32GB
- 2* LAN, onboard WiFi2.4G & BT4.1
- 2* RS232/ RS485
- 5* USB3.0, 1* USB2.0
- 1* HDMI, 1*VGA
- 1* Mini PCIE WiFi/ 4G slot
- 141.4 x 126 x 45.5mm
- DC 12V



C2120Z-V

- Intel® Elkhart Lake J6412
- 2* LAN (RTL8111H)
- 4* USB3.0
- 2* RS232 / RS485
- 1* HDMI2.0, 1* VGA
- 1* Mini PCIE WiFi/ 4G slot
- 141.4 x 126 x 45.5mm
- DC 12V



C2120Z-W4

- Intel® Alder Lake N97
- 4* LAN (Intel® 210AT)
- 2* RS232/ RS485
- 5* USB3.0, 1* USB2.0
- 1* HDMI1.4
- 1* Mini PCIE WiFi/ 4G slot
- 141.4 x 126 x 44mm
- DC 12~24V



C4350Z-H2

- Intel® Celeron 5205U / J6412 / Core i5-8260U / i5-10210U
- 2* LAN (RTL8111H)
- 2 * RS232 / RS485
- 4* USB3.0, 4* USB2.0
- 1* HDMI2.0, 1* HDMI1.4
- 1* M.2 WiFi, 1* mini PCIE WiFi / 4G slot
- 141.5 x 126 x 56.5mm
- DC 12V



C6850Z-C6

- Intel® J1900 / J6412 / i5-6300U / i5-8260U / i5-10210U / i5-1135G7 / i7-1195G7
- 2* LAN (Intel® 210AT)
- 8* USB
- 6* RS232 (4* RS485, 2* CAN)
- 1* HDMI, 1* VGA
- 1* M.2 WiFi, 1* mini PCIE 4G slot, 1* PS2, 1* TPM2.0, GPIO
- 235 x 197 x 57mm
- DC 9~36V



P1071Y-M6

- 10.4" LCD, 800*600, 4:3, capacitive touch screen
- Intel® Celeron J6412 / Core i5-8260U / i5-10210U / i5-1135G7
- 2* LAN (Intel® I210AT) M12 port
- 6* RS232 (2* RS485, 1* RS422) M12 port
- 4* USB3.0, 2* USB2.0 M12 port
- 1* HDMI
- 1* M.2 WiFi, 1* M.2 5G slot
- 272 x 214 x 62mm
- DC 9~36V M12 port



P1571Y-P4

- 10.4" / 12.1" / 15" / 15.6" / 17" / 19" / 21.5" / 23.8"
- IP65 front, Capacitive touch, Fanless design
- Intel® J6412 / i5-7300U / i5-8260U / i5-10210U / i5-1135G7
- 5* LAN(4* POE)
- 2* USB 3.0, 2* USB2.0, 4* RS232 (2* RS485, 1* RS422), 1* HDMI, GPIO
- 1* M.2 WiFi, 1* M.2 5G slot
- VESA mount/ Embedded
- DC 9~36V



P1581Y-C6

- 10.1" / 12.1" / 15.6" / 21.5" / 23.8" wide screen (Aspect Ratio 16:9)
- IP65 front, Capacitive touch, Fanless design
- Intel® J6412 / i5-7300U / i5-8260U / i5-10210U / i5-1135G7
- 2* LAN, 4* USB 3.0, 2* USB2.0
- 6* RS232 (2* RS485, 1* RS422), 1* HDMI, GPIO
- 1* M.2 WiFi, 1* M.2 5G slot
- VESA mount/ Embedded
- DC 9~36V



N5150Z

- Intel® Alder Lake N100
- 1* SO DDR4 RAM, up to 16GB, 1* M.2 SSD slot
- 2* LAN (RTL8111H)
- 2* HDMI2.0
- 3* USB3.0, 2* USB2.0, 1* Type-C
- 1* Audio, 1* WiFi
- 128 x 128 x 45mm
- DC 12V



N5450Z-HD2

- AMD® R5-7535HS CPU
- 2* SODIMM DDR5 RAM slots, 4800MHz, up to 64GB
- 2* RTL8125G 2.5G LAN port
- 2* HDMI2.0, 2* DP++
- 2* USB3.0, 2* USB2.0, 1* Type-C(10Gbps)
- 151 x 151 x 47mm
- DC 19V



G3250S-C6

- Intel® i5-7300HQ / i7-7820HQ / i5-8300H / i5-12450H
- 2* LAN (Intel® 210AT)
- 1* HDMI, 1*VGA
- 6* RS232 (6* RS485, 3* RS422, 2* CAN)
- 6* USB3.0, 2*USB2.0, 1* built-in USB2.0
- 1* Mini-PCIE WiFi/4G slot, 1* M.2 5G slot
- DC 9~36V



G3750S-C6

- Support Intel® LGA1151 / LGA1700, 6~9 / 11~12th Gen CPU (TDP < 65W)
- Intel Z390 / H770 chipset
- 2* LAN (Intel® I210AT)
- 1* HDMI, 1* VGA
- 2* SODIMM DDR4 slots, up to 64GB
- 6* RS232 (6* RS485, 3* RS422, 2* CAN)
- 8* USB3.0, 2* USB2.0, built-in 1* USB2.0
- 8* DI, 8* DO, isolated
- DC 9~36V



P6760S-L3

- Intel® Alder Lake N97 / N305
- 3* LAN (Intel® 210AT) (2*POE)
- 5* USB3.0, 5* USB2.0
- 6* RS232 / RS485
- 1* HDMI2.0, 1* DP
- 1* Mini-PCIE WiFi/ 4G slot
- Installation: Embedded/ Wall-mount/ DIN Rail
- 188 x 164.7 x 66mm
- DC 9~36V



G3780F-C8E2

- Chipset: H770, support Intel® LGA1700 12~14th Gen CPU
- 2* LAN (Intel® 210AT)
- 15* USB3.0, 3* USB2.0
- 8* RS232 (6* RS485 / 5* RS422/ 2* CAN)
- 1* HDMI, 1* VGA
- 1* mini PCIE WiFi, 1* M.2 WiFi, 1* M.2 5G slot
- 1* PCIe3.0 x16 (x8 signal), 1* PCIe3.0 x8 (x8 signal)
- 229 x 209 x 125.7mm
- DC 9~36V



G3780F-L6E2

- Chipset: H770, support Intel® LGA1700 12~14th Gen CPU
- 6* LAN (Intel® 210AT) (4* POE)
- 8* USB3.0, 3* USB2.0
- 4* RS232 (2* RS485, 1* RS422)
- 1* HDMI, 1* VGA
- 1* M.2 WiFi, 1* M.2 5G slot
- 1* PCIe3.0 x16 (x8 signal), 1* PCIe3.0 x8 (x8 signal)
- 229 x 209 x 125.7mm
- DC 9~36V